

Technical data

Art. no.	687701, Sound	
Gauge	H0e / TT / N	
PIN/Interface	6 pole	
According to NEM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	651
Cable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
DCC	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
MM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Load regulation	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
POM	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
NMRA compatible	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Speed steps (14, 28, 128)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Max. motor current	0.7 A	
Light and function outputs – of which outside interface	4, summary current: max. 0.5 A 2	
Max. decoder sum current	0.7 A	
Short-circuit protection of all outputs	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Dimensions	23 x 9 x 4 mm	
RailCom®	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Complies with ZIMO article	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	MX649N
Updatable	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Breaking section support		
Lenz ABC	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Märklin 72441/72442	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
ZIMO HLU	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Connection possibility for energy storage	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
Standard sound (Steam-, Diesel-, Electric locomotives)	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
Loudspeaker (is not included)	Art. no.: 10889	